

CHECKID-D1070

# MEDICAL EXAMINATION KIOSK

- This comprehensive health monitoring station reports patient data to your pharmacy system for actionable patient consulting.
- The product has passed ETL 60601 certification and is produced in strict accordance with ISO13485 medical system and MDSAP quality management system.



## HEALTH INDICATORS

BLOOD PRESSURE

HEIGHT

WEIGHT

BODY MASS INDEX BMI

BODY TEMPERATURE

BLOOD OXYGEN  
SATURATION

# FEATURES

- Overhead sensor measures height.
- Infrared sensor measures body temperature.
- Cuff measures blood pressure level and heart rate.
- Integrated body scale measures weight.
- Blood oxygen saturation sensor measures SpO2 value.
- Calculates Body Mass Index using the age, gender, height, and weight.

# SPECIFICATIONS

<b>MAIN CONTROL</b>	Industrial control motherboard, J6412, CPU main frequency 2.0GHz; 1 SO-DIMM 1 VGA, 1 HDMI; 9 USB interfaces, 4 RS232 interfaces, two 1000Mb adaptive Network cards, supporting TCP/IP protocol, DC12V Power on AutoStart, timed on/off function
<b>RAM</b>	LPDDR4 1600MHz
<b>HARD DISK</b>	256G SSD SATA
<b>MULTI-TOUCH</b>	10.1-inch with capacitive touch technology
<b>CAPACITIVE DISPLAY</b>	1280x800 resolution, USB Touch-Panel interface
<b>BLOOD PRESSURE NIBP</b>	USB interface, DC12V, roll type, arm circumference 16cm—43cm, 0mmhg-300mmhg, systolic blood pressure: 8.0-30.7KPA, diastolic pressure: 5.3-17.3KPA, (ATM. pressure)860HPA-1060HAP
<b>3 CHANNELS ECG</b>	Sampling 3 Leads simultaneously (1.5M cables)
<b>BLOOD OXYGEN</b>	USB interface, DC5V, blood oxygen saturation range 70%-100%. accuracy±2%
<b>WEIGHT</b>	RS485 interface, DC12V, range 200KG, accuracy 0.1KG
<b>HEIGHT</b>	RS485 interface, DC12V, measuring range 8-200CM, Accuracy 0.1CM
<b>ID/PASSPORT READER</b>	Support ID card and Passport scan, USB interface
<b>BODY TEMPERATURE</b>	USB interface, DC5V, temperature measurement range 34-42.9 degrees, infrared sensing, distance 5-15CM, Accuracy 0.2 °C
<b>RECEIPT PRINTER</b>	DC12V/2A, RS232/USB interface, paper width 58 mm, maximum roll diameter of 50mm, with paper near-end alarm, black mark detection & anti-jam funtion
<b>SPEAKERS</b>	Support multimedia voice system
<b>POWER SUPPLY VOLTAGE</b>	AC110V/220V, 300W